

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____



OUTDOOR UNIT FEATURES:

- ◆ Reliable and stable stepless inverter-driven technology.
- ◆ Anti-frost design includes an expanded heat exchanger, which provides a larger surface area for higher heat exchanging efficiency and smooth condensate drainage.
- ◆ 360°F refrigerant cooling technology safely and efficiently dissipates heat from the main PCB, inverter module, and outdoor unit electrical box.
- ◆ Intelligent defrosting mode utilizes 3 sensors to determine the optimal time to melt and remove frost from the outdoor unit.
- ◆ Static pressure of the outdoor unit up to 0.44 in.w.g.



Model name			CHV6-096URB	
Unit group configuration			1 x CHV6-096URB	
Nominal tonnage		RT	8	
Cooling capacity	Nominal capacity	Btu/h	92,000	
	Input power (Ducted/Non-ducted)	kW	7.80 / 6.55	
	EER (Ducted/Non-ducted)	Btu/h	11.80 / 14.05	
	IEER (Ducted/Non-ducted)	Btu/h	23.40 / 32.00	
Heating capacity	Nominal capacity	Btu/h	100,000	
	Input power (Ducted/Non-ducted)	kW	7.96 / 7.15	
	COP 47°F (Ducted/Non-ducted)	W/W	3.68 / 4.10	
	Low temperature heating capacity (17°F)	Btu/h	70,000	
	Input power 17°F	kW	8.58 / 7.74	
	COP 17°F (Ducted/Non-ducted)	W/W	2.39 / 2.65	
Power supply		V, Ph, Hz	208/230V, 3Ph, 60Hz	
Max/Min power supply		V	253 / 188	
Electrical parameters	MCA	A	41.2	
	MOP	A	50	
Min/Max number of connectable indoor units		#	1 / 16	
Total indoor unit capacity		%	50~150% to outdoor unit capacity	
Dimensions (H x W x D)		in	68 1/8 x 37 13/32 x 29 17/32	
Connection pipe diameter	Heat recovery operation system	Low pressure gas pipe	in	7/8"
		High/Low pressure gas pipe	in	3/4"
		Liquid pipe	in	3/8"
	Heat pump operation system	Low pressure gas pipe	in	7/8"
		Liquid pipe	in	3/8"
Refrigerant			R410A	
Compressor			Scroll Comp	
Compressor quantity			1	
Refrigerant charge before shipment		lbs	13.2	
Weight	Net weight	lbs	536	
	Gross weight	lbs	597	
Total piping length		ft	3,280	
Height difference	Maximum below unit	ft	164 (295* see note)	
	Maximum above unit	ft	131 (295* see note)	
	Between IDUs	ft	49 (98* see note)	

* Note: maximum height difference can be expanded with assistance from C&H technical support team.

Fan motor	Quantity	#	1
	Air flow rate	CFM	6,460
Sound pressure level		dB(A)	60
Operation range	Cooling	°F DB	14 ~ 126
	Heating	°F DB	-13 ~ 62
AHRI Certification	Ducted		208119928
	Non-Ducted		208119929
	Mixed ducted and non-ducted		208119940

NOTES:

- The above specifications demonstrate cooling and heating conditions when the outdoor unit is operated with the 100% rating of indoor units, Cooling operation conditions: indoor air inlet temperature: 80°F DB 67°F WB, Outdoor air inlet temperature: 95°F DB, Piping length: 25ft., Piping lift: 0ft.
Heating operation conditions: Nominal heating condition, indoor air inlet temperature: 70°F DB, outdoor air inlet temperature: 47°F DB 43°F WB.
Heating operation conditions: Low temp. heating condition, indoor air inlet temperature: 70°F DB, outdoor air inlet temperature: 17°F DB 15°F WB.
- Rated capacity and efficiency are certified under AHRI Standard 1230. Ratings are subject to change without notice. Current certified ratings are available at www.ahridirectory.org.
- The above noise values were measured in an anechoic chamber without reflected echo. Measurement point: 3.3ft from the service cover surface and 4.9ft from floor level.
- The final appearance of outdoor units may vary from images shown here.

Unit: inch (mm)

