

HEAT PUMP PORTABLE AIR CONDITIONERS

















CH-PDH14AC3

* ≈ DUAL HOSE

CH-STLS-14AC

CH









Functions 3 in 1: Cooling, Heating and Dehumidifying **Auto Restart Function** Omni-Directional Caster Flexible Installation Self-Diagnosis and Auto Protection Timer Self-Evaporative System Refrigerant Leakage Detection Convenient Handle

Model	CH-PDH14AC3	CH-STLS-14AC
Cooling Capacity by ASHRAE Standard	14,000 Btu/h	14,000 Btu/h
Cooling Capacity by SACC Standard	7,000 Btu/h	12,000 Btu/h
Heating Capacity	11,000 Btu/h	12,000 Btu/h
CEER	5.93	8.9
МОСР	13.5A	15
Rated Input Current	11.4A	2.40/5.65
LCDI Plug	15A	5-15P
Compressor Type	Rotary	Inverter
Power Cord Length	6ft	5.58 Ft.
CFM	200	226
Power Consumption (95°)	1,450W,	1,450W,
Exhaust System Type	Dual Hose	Hose in Hose
Fan Speeds - Cool/Fan/Heat	3	3
Adjustable Air Louver	Yes	Yes
Direct Drain	Yes	Yes
Electronic/Mechanical	Electronic, LED Display	Electronic, LED Display
Voltage/Frequency	115V/60Hz	115V/60Hz
Application Area	450 Sq. Ft.	550 Sq. Ft.
Refrigerant	R-410A, 22.5oz	R32, 17oz
Design Pressure (Hi/Lo)	523/236 PSIG	550/340 PSIG
Timer	24h	24h
Working Temperature	C: 61°F - 89°F / H:61°F-77°F	C:62°F - 95°F / H:41°F-86°F
Dehumidification Capacity	91.2 Pints/Day	65 Pints/Day
Unit Dimensions WxHxD	17.4x29.4x16.2 inch	19.53x16.73x32.48
Package Dimensions WxHxD	19.9x34.2x18.1 inch	22.24x18.07x34.45
Net Weight	76.3 lb	77.16









